

TP102V Thermal Vacuum Plate

INSTECH® FOCUS ON EXCELLENCE



#TP102V-60417

Features

- Peltier Based Thermal Plate with Sealed Sample Chamber for Vacuum
- Programmable Precision Temperature Control from -40 °C to 90 °C with 0.1 °C Temperature Precision
- Large Viewing Aperture for Reflected Light
- Large Sample Area
- Controlled Fast Heating and Cooling Rate
- Optional Two Electric Feed-Through Leads for Sample Probing
- Configured with STC200 Standalone Temperature Controller with RS232 Communication Port and Windows Based Software
- Optional IEEE488 Communication Port
- Free LabVIEW Drivers for IEEE488 and RS232



Technical Specification

Temperature Control Sensor	Platinum RTD
Temperature Range	-40 °C to 90 °C
Temperature Precision	0.1 °C
Temperature Stability	±0.1 °C at 37 °C
Minimum Working Distance	6.6 mm
Sample Area	1" x 3.5"
Sample View Aperture (Reflected Light)	26.5 mm
Vacuum Port	1/8 NPT Female
Gauge Port	1/8 NPT Female

Ordering Information

Part Number	Description
TP102V-STC20A	TP102V vacuum thermal plate with STC200 temperature controller. RS232 communication port, with Win-Temp software. 115V input power.
TP102V-STC20U	TP102V vacuum thermal plate with STC200 temperature controller. RS232 communication port, with Win-Temp software. 230V input power
F2V-TP102V	Two electric lead feed-through for TP102V

Accessories

Optional Parts for STC200	Please refer to the STC200 Temperature Controller brochure for add-on STC200 controller optional parts (e.g. IEEE-STC200: IEEE 488 communication port).
---------------------------	---

www.instec.com e-mail: sales@instec.com tel: +1 303-444-4608 fax: +1 303-444-4607

Instec, Inc. 5589 Arapahoe Avenue #208 Boulder Colorado 80303 USA

Contact Instec today for further product information. Inquires for a hot and cold stage, a hot and cold chuck, a hot and cold plate, and/or the liquid crystal testing products customized to your special requirements are also welcome. Above information is subject to changes without notice.